



ENDLESS POLYESTER WEB-SLING

	Part Number	Web Width (in.)	Rated Capacity (lbs)		
			Vertical	Choker	V. Basket
One Ply	PEN1-901	1	3,200	2,500	6,400
	PEN1-902	2	6,400	5,000	12,800
	PEN1-903	3	8,800	7,040	17,600
	PEN1-904	4	11,500	9,200	23,000
	PEN1-906	6	16,500	13,200	33,000
	PEN1-908	8	19,200	15,400	38,400
	PEN1-910	10	22,400	17,900	44,800
	PEN1-912	12	26,900	21,500	53,800
Two Ply	PEN2-901	1	6,200	4,900	12,400
	PEN2-902	2	12,400	9,900	24,800
	PEN2-903	3	16,300	13,000	32,600
	PEN2-904	4	20,700	16,500	41,400
	PEN2-906	6	28,600	23,000	57,200
	PEN2-908	8	30,700	24,500	61,400
	PEN2-910	10	33,600	26,800	67,200
	PEN2-912	12	37,600	30,000	75,200
Three Ply	PEN3-901	1	8,000	6,400	16,000
	PEN3-902	2	16,000	12,800	32,000
	PEN3-903	3	21,500	17,200	43,000
	PEN3-904	4	28,700	23,000	57,400
	PEN3-906	6	40,700	32,500	81,400
	PEN3-908	8	46,000	36,800	92,000
	PEN3-910	10	51,500	41,200	103,000
	PEN3-912	12	59,200	47,300	118,400
Four Ply	PEN4-901	1	10,000	8,000	20,000
	PEN4-902	2	19,800	15,800	39,600
	PEN4-903	3	26,700	21,300	53,400
	PEN4-904	4	35,600	28,400	71,200
	PEN4-906	6	50,500	40,400	101,000
	PEN4-908	8	57,600	46,000	115,200
	PEN4-910	10	67,200	53,700	134,400
	PEN4-912	12	80,700	64,500	161,400

WARNING

Do not exceed rated capacities.

Sling capacity decreases as the angle from horizontal decreases.

Slings should never be used at angles less than 30 degrees.



POLYESTER WEB-SLING

X can equal either flat or twisted eyes, if customer wants twisted it must be specified. Provide required length when ordering.

	Part Number	Web Width (in.)	Rated Capacity (lbs)		
			Vertical	Choker	V. Basket
One Ply	PEEX1-901	1	1,600	1,250	3,200
	PEEX1-902	2	3,200	2,500	6,400
	PEEX1-903	3	4,800	3,800	9,600
	PEEX1-904	4	6,400	5,000	12,800
	PEEX1-906	6	9,600	7,700	19,200
	PEEX1-908	8	12,800	10,200	25,600
	PEEX1-910	10	16,000	12,800	32,000
	PEEX1-912	12	19,200	15,400	38,400
Two Ply	PEEX2-901	1	3,200	2,500	6,400
	PEEX2-902	2	6,400	5,000	12,800
	PEEX2-903	3	8,600	6,900	17,200
	PEEX2-904	4	11,500	9,200	23,000
	PEEX2-906	6	16,300	13,000	32,600
	PEEX2-908	8	19,200	15,400	38,400
	PEEX2-910	10	22,400	17,900	44,800
	PEEX2-912	12	26,900	21,500	53,800
Three Ply	PEEX3-901	1	4,100	3,300	8,200
	PEEX3-902	2	8,300	6,600	16,600
	PEEX3-903	3	12,500	10,000	25,000
	PEEX3-904	4	16,000	12,800	32,000
	PEEX3-906	6	23,000	18,400	46,000
	PEEX3-908	8	30,700	24,500	61,400
	PEEX3-910	10	36,800	29,400	73,600
	PEEX3-912	12	44,000	35,200	88,000
Four Ply	PEEX4-901	1	5,000	4,000	10,000
	PEEX4-902	2	10,000	8,000	20,000
	PEEX4-903	3	14,900	11,900	29,800
	PEEX4-904	4	19,800	15,800	39,600
	PEEX4-906	6	29,800	23,800	59,600
	PEEX4-908	8	39,700	31,700	79,400
	PEEX4-910	10	49,600	39,600	99,200
	PEEX4-912	12	59,500	47,600	119,000



WARNING

Do not exceed rated capacities.

Sling capacity decreases as the angle from horizontal decreases.

Slings should never be used at angles less than 30 degrees.



Eye length (Applies to all Web slings)

Plies of Web	SLING WIDTH (In.)							
	1	2	3	4	6	8	10	12
1	8 1/2	10	11	12	16	20	24	24
2	8 1/2	10	11	12	16	20	24	24
3	10	12	14	16	18	24	24	24
4	10	12	14	16	18	24	24	24